


U-profilý dle DIN 1026:

Materiály:

AISI 304/L (DIN 1.4301/7)
 AISI 316/L (DIN 1.4401/4)
 AISI 316Ti (DIN 1.4571)

Specifikace:

ohýbané: délka cca 6 m
 za tepla válcované: délka cca 4-7 m
Certifikát:
 na přání dle EN 10204 3.1



H		B		S		T	kg/m
20	x	10	x	3,0	x	3,0	0,82
20	x	20	x	2,0	x	2,0	0,83
20	x	20	x	3,0	x	3,0	1,30
25	x	15	x	3,0	x	3,0	1,18
25	x	25	x	3,0	x	3,0	1,66
30	x	15	x	3,0	x	3,0	1,30
30	x	15	x	4,0	x	4,0	1,66
30	x	20	x	3,0	x	3,0	1,54
30	x	30	x	2,0	x	2,0	1,31
30	x	30	x	3,0	x	3,0	2,63
30	x	30	x	4,0	x	4,0	2,63
30	x	33	x	5,0	x	7,0	4,30
40	x	20	x	2,0	x	2,0	1,47
40	x	20	x	3,0	x	3,0	1,78
40	x	20	x	4,0	x	4,0	2,30
40	x	30	x	3,0	x	3,0	2,26
40	x	30	x	4,0	x	4,0	2,94
40	x	35	x	5,0	x	7,0	4,80
40	x	40	x	3,0	x	3,0	2,59
40	x	40	x	4,0	x	4,0	3,33
50	x	25	x	3,0	x	3,0	2,26
50	x	25	x	4,0	x	4,0	2,94
50	x	25	x	5,0	x	6,0	4,20
50	x	30	x	3,0	x	3,0	2,50
50	x	30	x	4,0	x	4,0	3,26
50	x	38	x	5,0	x	7,0	5,70
50	x	40	x	3,0	x	3,0	2,98
50	x	40	x	4,0	x	4,0	3,90
50	x	50	x	3,0	x	3,0	3,31
50	x	50	x	4,0	x	4,0	4,29
50	x	50	x	5,0	x	5,0	5,36
60	x	30	x	3,0	x	3,0	2,59
60	x	30	x	4,0	x	4,0	5,74
60	x	30	x	6,0	x	6,0	5,10
60	x	40	x	3,0	x	3,0	6,08

H		B		S		T	kg/m
60	x	40	x	4,0	x	4,0	4,20
60	x	40	x	6,0	x	6,0	6,08
60	x	60	x	6,0	x	6,0	7,22
65	x	42	x	5,5	x	7,5	7,40
80	x	40	x	3,0	x	3,0	5,46
80	x	40	x	4,0	x	4,0	4,60
80	x	40	x	5,0	x	5,0	5,96
80	x	40	x	6,0	x	6,0	7,20
80	x	40	x	8,0	x	8,0	9,60
80	x	45	x	6,0	x	8,0	8,80
100	x	50	x	3,0	x	3,0	4,51
100	x	50	x	4,0	x	4,0	5,89
100	x	50	x	5,0	x	5,0	7,53
100	x	50	x	6,0	x	6,0	8,97
100	x	50	x	6,0	x	8,5	10,60
100	x	50	x	8,0	x	8,0	12,13
120	x	55	x	7,0	x	9,0	13,50
120	x	60	x	6,0	x	6,0	10,90
130	x	65	x	6,0	x	6,0	11,90
140	x	60	x	7,0	x	10,0	16,20
140	x	70	x	7,0	x	7,0	14,90
150	x	75	x	6,0	x	6,0	13,90
150	x	75	x	9,0	x	9,0	20,10
160	x	65	x	7,5	x	10,5	19,10
160	x	80	x	6,0	x	6,0	14,90
160	x	80	x	8,0	x	8,0	19,40